



AGM BATTERY: UN SERIES

SPECIFICATIONS

Battery Type	Nominal Voltage (V)	Capacity (Ah)	Dimension(± 1mm)								Weight		Terminal Type
			Length		Width		Height		Total Height		kg	pound	
			mm	in	mm	in	mm	in	mm	in			
UN0.5-6	6	0.5	57	2.24	14	0.55	51	2.01	51	2.01	0.10	0.22	T24
UN1.2-6	6	1.2	97	3.82	24	0.94	52	2.05	58	2.28	0.30	0.66	F1/T21
UN1.2-6S	6	1.2	97	3.82	24	0.94	50	1.97	56	2.20	0.30	0.66	F1
UN2.0-6	6	2.0	43	1.69	37	1.46	76	2.99	76	2.99	0.31	0.68	T5
UN2.8-6	6	2.8	66	2.60	33	1.30	97	3.82	104	4.09	0.55	1.21	F1
UN3.2-6	6	3.2	134	5.28	34	1.34	61	2.40	67	2.64	0.65	1.43	F1
UN4-6	6	4.0	70	2.76	47	1.85	101	3.98	107	4.21	0.66	1.45	F1
UN4.5-6	6	4.5	70	2.76	47	1.85	101	3.98	107	4.21	0.76	1.68	F1
UN5-6	6	5.0	70	2.76	47	1.85	101	3.98	107	4.21	0.81	1.79	F1
UN5-6S	6	5.0	67	2.64	67	2.64	96	3.78	109	4.29	0.81	1.79	T7
UN5.6-6	6	5.6	70	2.76	47	1.85	101	3.98	107	4.21	0.82	1.81	F1
UN7-6	6	7.0	151	5.94	34	1.34	94	3.70	100	3.94	1.08	2.38	F2
UN8-6	6	8.0	151	5.94	34	1.34	94	3.70	100	3.94	1.23	2.71	F2
UN10-6	6	10.0	151	5.94	50	1.97	94	3.70	100	3.94	1.65	3.64	F2
UN12-6	6	12.0	151	5.94	50	1.97	94	3.70	100	3.94	1.80	3.97	F2
UN14-6TS	6	14.0	108	4.25	71	2.80	140	5.51	140	5.51	2.30	5.07	T8
UN14-6TS-H	6	14.0	108	4.25	71	2.80	140	5.51	140	5.51	2.30	5.07	T20
UN14-6T	6	14.0	108	4.25	71	2.80	140	5.51	140	5.51	2.30	5.07	F1/F2
UN14-6TS-J	6	14.0	108	4.25	71	2.80	140	5.51	140	5.51	2.30	5.07	T26
UN180-6X	6	180.0	306	12.05	168	6.61	220	8.66	226	8.90	26.80	59.08	F12
UN200-6X	6	200.0	306	12.05	168	6.61	220	8.66	226	8.90	28.00	61.73	F12
UN225-6X	6	225.0	320	12.60	176	6.93	225	8.86	229	9.02	31.00	68.34	F12
UN3.2-8S	8	3.2	134	5.28	36	1.42	63	2.48	69	2.72	0.78	1.72	F1
UN0.8-12	12	0.8	96	3.78	25	0.98	62	2.44	62	2.44	0.33	0.73	T13/T9
UN1.2-12	12	1.2	97	3.82	43	1.69	52	2.05	58	2.28	0.59	1.30	F1
UN2.0-12C	12	1.6	144	5.67	24	0.94	65	2.56	65	2.56	0.58	1.28	T10
UN2.0-12M	12	1.6	150	5.90	20	0.79	90	3.54	90	3.54	0.70	1.54	T11
UN2.3-12C	12	2.0	182	7.17	24	0.94	61	2.40	61	2.40	0.76	1.68	T10
UN2.3-12	12	2.3	178	7.01	35	1.38	61	2.40	67	2.64	0.99	2.18	F1
UN2.5-12	12	2.5	104	4.09	48	1.89	70	2.76	70	2.76	0.90	1.98	T16